

Quotation Request WORKSHEET

XENFLEX™

FILL-IN, FAX BACK

Customer _____ Your Name _____
 Job Name _____ Address _____
 Job Location _____







 Phone _____ Fax _____
 Date Need _____ Today's Date _____ Email _____

Ordering Guide

PROFILE	SPACING	WATTAGE	LENGTH	VOLTAGE
XF	<input type="checkbox"/> 2" <input type="checkbox"/> 3" <input type="checkbox"/> 4" <input type="checkbox"/> 6"	Clear <input type="checkbox"/> 5 <input type="checkbox"/> 10 Frosted <input type="checkbox"/> 5F <input type="checkbox"/> 10F	_____(in.) Specify overall length in inches	<input type="checkbox"/> 24 (Std) <input type="checkbox"/> 12

Refer to:
Data Tables (next page) for Length and Wattage limits.
XENFLEX Catalog (PDF download) for additional information.


SPECIFICATION OF MODULES MAY AFFECT ALLOWABLE OVERALL RUN LENGTH.

OPTIONS			
EXTRUSION	LENSES*	XENTRAC MODULES	REFLECTORS**
<input type="checkbox"/> XF-XTW White	For use w/ XENFLEX Strip	MR-11 (XF-MR11)	<input type="checkbox"/> White Symmetric (XF-SYW) 
<input type="checkbox"/> XF-XTC Chrome	<input type="checkbox"/> XF-L (5 Watt)	<input type="checkbox"/> 20 Watt <input type="checkbox"/> 35 Watt	<input type="checkbox"/> White Asymmetric (XF-ASW) 
<input type="checkbox"/> XF-XTB Brass	<input type="checkbox"/> XF-L10 (10 Watt)	MR-16 (XF-MR16)	<input type="checkbox"/> Brass Symmetric (XF-SYB) 
	For use w/ Extrusion	<input type="checkbox"/> 20W <input type="checkbox"/> 35W <input type="checkbox"/> 50W	<input type="checkbox"/> Brass Asymmetric (XF-ASB) 
	<input type="checkbox"/> XF-XTL (5 Watt)	AR (XF-AR)	<input type="checkbox"/> Chrome Parabolic (XF-PAR) 
	<input type="checkbox"/> XF-XTL10 (10 Watt)	<input type="checkbox"/> 20 Watt <input type="checkbox"/> 50 Watt	<input type="checkbox"/> Half Chrome Parabolic (XF-HPR) 


* 5 Watt: Continuous Lens. 10 Watt: Individual Lamp Lenses.
 ** Not for use with Lenses or Modules.

Mounting Orientation

Curvable Mount



Non-Curvable Mount



XENFLEX cannot curve in this mounting position.

TRANSFORMER

QTY

Please indicate Transformer locations in sketch area to the right.

▼ Specific layout and run lengths are required. Diagram below or attach blueprint / sketch.



7 DONNA DRIVE
 WOOD-RIDGE, NJ 07075

TOLL FREE 800-443-8823
 FAX 201-438-9541

INTERNET www.starfirelighting.com
 E-MAIL info@starfirelighting.com

Max. Run Length

LAMP WATTAGE	SPACING	MAX LENGTH 24V	MAX LENGTH 12V	WATTS/FT	LUMENS/FT
5	2"	20'	10'	30	300
	3"	30'	15'	20	200
	4"	40'	20'	15	150
	6"	60'	30'	10	100
10	2"	10'	5'	60	900
	3"	15'	7.5'	40	600
	4"	20'	10'	30	450
	6"	30'	15'	20	300

Transformers

CAT. NO.	WATTAGE	WEIGHT	DIMENSIONS (LxWxD)
XTR-100	100	4.5 Lbs	8" x 3.5" x 3.625"
XTR-250	250	5 Lbs	8" x 4.188" x 3.875"
XTR-500	500	8 Lbs	11.5" x 4.313" x 4.625"
XTR-750	750	21.5 Lbs	12" x 6.063" x 5.625"
XTR-1000	1000	22 Lbs	12" x 6.063" x 5.625"
XTR-1500	1500	30 Lbs	11.625" x 5.438" x 4.875"
XTR-2000	2000	35 Lbs	13.25" x 5.438" x 4.875"