1" LED Wet Location Surface Mount

LED



Linear Narrow Profile
LED Direct Surface Mount with Flush Lens and External Driver for Wet Locations

SDXW1

Job Name

Fixture Type



Fixture Profile



Sectional Side View

Remote Driver Enclosure

NEMA enclosure required for wet locations



Profile



Sectinal Side View

SDXW1- L [ ] [ ] [ ] [ ] - [ ] - [ ] [ ]

CRI	Color	Output	Dimming	Lens	Length (")	Cbl. Feed	Finish
8 80+ **9** 90+ **R** RGB & RGBW	**27** 2700K *(90CRI only)* **30** 3000K **35** 3500K **40** 4000K **TW** Tunable White [1] [2] **DW** Dim-to-Warm [1] [2] **GB** RGB **G3** RGBW 3000K **G5** RGBW 3500K	**S** Standard **H** High **M** Maximum *Custom:* *Specify Lm/Ft* [3] **F** Fixed *(RGBs)*	**S** Std. 0-10V 1% **O** Dim-to-Off [1] [2] **L** Lutron 1% [3] **D** DALI 1% **P** PoE [3] **2** Wire *(phase-cut)* **T** Step *(10%-70%)* **W** Wireless [3] **X** DMX *(RGBs)*	**DF** Diffuser **AS** Asymmetric **BW** Batwing	*Nominal:* **24** [5] **36** **48** **60** **72** **84** **96** *(see Page 2)* *Custom:* **Cxxx** *(in inches)* [3]	**T** Top, Std. **E** End	**W** White, Std. **B** Black *Custom Color: Specify RAL#*

Product Code Example: **SDXW1-L830HSDF-C120-TW**

A wet location, ultra-clean line, low profile, narrow aperture, linear surface mount fixture utilizing high performance LED boards and lenses. Extruded aluminum housing with external driver. Special sealants and gaskets allow for use in wet locations (horizontal mount lens facing down only).

Features

- Starfire's proprietary EvenGlow™ system provides uniform lens illumination from edge-to-edge without lamp imaging, bright spots or shadows at any length.
- Fixtures fabricated to any specified length without custom engineering, maximum 96" per section.
- Multiple sections can be joined having a single power feed (lenses are not continuous).
- Exceptional lumen per watt efficiency.
- High efficiency, low cost, dynamic Tunable White and Dim-to-Warm options.
- High performance acrylic flush diffusion, batwing or asymmetric lens.

Fixture Specifications

- Housing: Heavy-duty extruded aluminum.
- Finish: White (std), custom available.
- Weight: Approx. 1 lb per linear foot.
- UL Listed, Wet Location.
- IP65 design rating.

Electrical

- Power consumption: Per specification based on LED configuration.
- Input Voltage: 120-277V universal driver.
- Ambient operating range: -4 °F to +100 °F
- Remote electronic driver(s).
- Class 2 plenum wiring between fixture and remote driver.
- Dimming: 0-10V 1% standard, consult factory for other options.

LED Specifications/Photomerty: Page 2

Mounting

- Screw-mount housing to blocking (by others). Consult factory for special ceiling conditions.
- External driver must be mounted in NEMA enclosure for wet locations (by others).

Options (Consult Factory)

- Occupancy sensor, daylight control module [4]
- EM battery pack in 4ft segments. Delivers 1000+ total lumens for 90 mins (depending upon configuration). Specify location.
  Status Indicator/Test Button in remote water tight box with clear cover.
- BAA/BABA compliance for some configurations – factory will advise.

[1] 90 CRI, 2700K-6500K std, others availablle, Specify CCT range.
[2] 0-10V Control std, others available - Specify (Factory to confirm).
[3] Specify – Factory to confirm.
[4] Sensor must be wet location rated.
[5] Available in output levels of 400 lm/ft or greater only.

STARFIRE LIGHTING, INC.
7 Donna Drive, Wood-Ridge, NJ 07075
starfirelighting.com

P 201.438.9540
F 201.438.9541

All designs and drawings are the property of STARFIRE LIGHTING, INC. We reserve the right to make changes to specifications and approved designs at any time without notice to facilitate manufacturing methods to the extent that such changes do not compromise design integrity. All performance specifications are subject to +/- 10% deviation.

SDNW1

LED Strip

High output edge-to-edge, end-to-end illumination

- Choice of lumen output levels:
  S: Standard, **H:** High, **M:** Maximum
  C: Custom (between 200 and 1100 Lm/Ft) depending upon LED Configuration.
- **High Output Option***: Up to 1800 Lm/Ft, consult factory.
- LED Efficiency: Up to 160 Lm/Wt at Maximum output and 180 Lm/Wt at Standard power (at 80+ CRI).
- Proprietary in-house, ultra-tight Vf binned LEDs for uniform intensity.
- Color Consistency**: Equal or better than 3 SCDM.
- Tunable Range: 2700K-6500K, other ranges available.
- Dim-to-Warm: Warm range down to 1800K.
- L70: 50,000+ hours at Maximum output
- 5 year limited warranty***

Fixture Dimensions

Fixture Overall Length

Nominal	Actual
24"	24.34"
36"	33.62"
48"	48.06"
60"	55.67"
72"	71.81"
84"	83.22"
96"	95.34"

Fixture Length Example:
To order a nominal 36" length (33.62" exact): enter **36**
For an exact 36" length: enter **C36**

Consult factory for fixture installation dimensions.
Some exact lengths may include unobtrusive lens filler

RGB & RGBW LEDs

Maximum Output (Diffuser)

	Lm/Ft	Wt/Ft	Lm/Wt
RGB (all on)	123	9.4	6.0
White	467	6.8	8.4
RGBW (all on)	617	16.2	38.0

Output adjustable with DMX-512 Control

Diffuser



Diffuser

80 CRI		4000		3500		3000		2700	
Settings	Lm/ft	Wt/Ft	Lm/Wt	Wt/Ft	Lm/Wt	Wt/Ft	Lm/Wt	Wt/Ft	Lm/Wt
S	250	1.7	147.4	1.7	143.3	1.8	139.3	1.9	129.9
H	500	3.5	144.0	3.6	139.9	3.7	135.9	4.0	125.9
M	750	5.3	140.6	5.5	136.5	5.7	132.5	6.2	121.8

LV6

Batwing



Batwing

80 CRI		4000		3500		3000		2700	
Settings	Lm/ft	Wt/Ft	Lm/Wt	Wt/Ft	Lm/Wt	Wt/Ft	Lm/Wt	Wt/Ft	Lm/Wt
S	250	1.7	143.6	1.8	139.7	1.8	135.7	2.0	126.6
H	500	3.6	140.2	3.7	136.3	3.8	132.3	4.1	122.5
M	750	5.5	136.8	5.6	132.9	5.8	128.9	6.3	118.4

LV6

Asymmetric



Asymmetric

80 CRI		4000		3500		3000		2700	
Settings	Lm/ft	Wt/Ft	Lm/Wt	Wt/Ft	Lm/Wt	Wt/Ft	Lm/Wt	Wt/Ft	Lm/Wt
S	250	1.7	147.5	1.7	143.5	1.8	139.5	1.9	130.1
H	500	3.5	144.1	3.6	140.1	3.7	136.1	4.0	126.0
M	750	5.3	140.7	5.5	136.7	5.7	132.6	6.2	121.9

LV6

* Consult factory for High Output White channel 1200+ Lm/Ft
** Does not apply to Tunable White
*** See Starfire website for Product Limited Warranty

IP 65

STARFIRE LIGHTING, INC.
7 Donna Drive, Wood-Ridge, NJ 07075
starfirelighting.com

P 201.438.9540
F 201.438.9541

All designs and drawings are the property of STARFIRE LIGHTING, INC. We reserve the right to make changes to specifications and approved designs at any time without notice to facilitate manufacturing methods to the extent that such changes do not compromise design integrity. All performance specifications are subject to +/- 10% deviation.