6" VersaLux LED Wet Location, Surface Mount

LED



Linear LED Direct Surface Mount with Flush Lens and Internal Driver for Wet Locations

SDW6

Job Name

Fixture Type



Fixture Profile



Sectional Side View

SDW6- ____ ____ ____ ____ - ____ - ____ - ____ ____

CRI	Color	Output	Dimming	Lens	Length (")	Cbl. Feed	Finish
8 80+ **9** 90+ **R** RGB & RGBW	**27** 2700K *(90CRI only)* **30** 3000K **35** 3500K **40** 4000K **TW** Tunable White [1] [2] **DW** Dim-to-Warm [1] [2] **GB** RGB **G3** RGBW 3000K **G5** RGBW 3500K	**S** Standard **H** High **M** Maximum *Custom:* *Specify Lm/Ft* [3] **F** Fixed *(RGBs)*	**S** Std. 0-10V 1% **O** Dim-to-Off [1] [2] **L** Lutron 1% [3] **D** DALI 1% **P** PoE [3] **2** Wire *(phase-cut)* **T** Step *(10%-70%)* **W** Wireless [3] **X** DMX *(RGBs)*	**DF** Diffuser **AS** Asymmetric **BW** Batwing	*Nominal:* **24** **36** **48** **60** **72** **84** **96** *(see Page 2)* *Custom:* **Cxxx** *(in inches)* [3]	**T** Top, Std. **E** End	**W** White, Std. **B** Black *Custom Color: Specify RAL#*

Product Code Example: **SDW6-830HD-DF-C120-TW**

A wet location, ultra-clean line, low profile, linear surface mount fixture, utilizing high performance LED boards and lenses. Extruded aluminum housing with internal driver. Special sealants and gaskets allow for use in wet locations (horizontal mount lens facing down only).

Features

- Starfire's proprietary EvenGlow™ system provides uniform illumination from end-to-end without lamp imaging, bright spots or shadows at any length.
- Fixtures fabricated to any specified length without custom engineering, 96" per section.
- Multiple sections can be joined having a single power feed. Lenses are not continuous.
- Exceptional lumen per watt efficiency.
- High efficiency, low cost, Tunable White, Dim-to-Warm and Dim-toOff options.
- High performance snap-in lenses; flush diffusion, batwing or asymmetric.

Fixture Specifications

- Housing/Trim: Heavy-duty extruded aluminum.
- Finish: White (std), custom available.
- Weight: Approx. 3.8 lbs. per linear foot.
- UL Listed, Wet Location.
- IP65 design rating.

Electrical

- Power consumption: Per specification based on LED configuration.
- Input Voltage: 120-277V universal driver.
- Ambient operating range: -4° F to 100 °F.
- Integral wiring buss between fixture sections.
- Integral electronic drivers.
- RGB & RGBW Power Supply and DMX Decoder are external.
- Dimming: 0-10V 1% standard, consult factory for options.

Mounting

- Screw mount housing to blocking.
- Contact factory for special ceiling conditions.

Options (Consult Factory)

- Occupancy sensor, daylight control module [4]
- EM battery pack in 4ft segments. Delivers 1000+ total lumens for 90 mins (depending upon configuration). Specify location at time of order.
- Status Indicator/Test Button in remote water-tight box with clear cover.
- BAA/BABA compliance for some configurations – factory will advise.

LED Specifications/Photometry: Page 2

[1] 90 CRI, 2700K-6500K std., others available. Specify CCT range.
[2] 0-10V Control, std., others available . Specify (factory to confirm).
[3] Specify – Factory to confirm.
[4] Sensor must be wet location rated

STARFIRE LIGHTING, INC.
7 Donna Drive, Wood-Ridge, NJ 07075
starfirelighting.com

P 201.438.9540
F 201.438.9541

All designs and drawings are the property of STARFIRE LIGHTING, INC. We reserve the right to make changes to specifications and approved designs at any time without notice to facilitate manufacturing methods to the extent that such changes do not compromise design integrity. All performance specifications are subject to +/- 10% deviation.

SDW6 LED

LED Strip

High output edge-to-edge, end-to-end illumination

- Choice of lumen output levels: **S**tandard, **H**igh, **M**ax and **C**ustom (between 400 and 1000 Lm/Ft) depending upon configuration.
- **High Output option***: Up to 1800 Lm/Ft, consult factory.
- LED efficiency: Up to 160 Lm/Wt at Maximum output and 180 Lm/Wt at Standard Power (at 80+ CRI).
- Proprietary in-house, ultra-tight Vf binned LEDs for uniform intensity.
- Color consistency**: Equal or better than 3 SCDM.
- Tunable Range: 2700K-6500K, other ranges available.
- Dim-to-Warm – Warm range down to 1800K.
- L70: 50,000+ hours at Maximum output.
- 5 year limited warranty***

Fixture Dimensions

Fixture Overall Length

Nominal	Actual
24"	23.5"
36"	34.5"
48"	45.5"
60"	56.5"
72"	72"
84"	84"
96"	95"

Fixture Length Ordering Example:
For a nominal 36" length (34.5" exact): enter **36**.
To order an exact 36" length: enter **C36**.
Consult factory for fixture installation dimensions.

White LED Specifications

Diffusor – White LEDs

80 CRI		4000K		3500K		3000K		2700K (90 CRI)	
Output Setting	**Lm/Ft**	**Wt/Ft**	**Lm/Wt**	**Wt/Ft**	**Lm/Wt**	**Wt/Ft**	**Lm/Wt**	**Wt/Ft**	**Lm/Wt**
S Standard	**550**	3.9	141.3	4.0	137.3	4.1	133.3	4.5	123.3
H High	**950**	7.0	135.9	7.2	131.9	7.4	127.9	8.1	116.8
M Maximum	**1020**	7.6	134.9	7.8	130.9	8.0	126.9	8.8	115.6

LV6

Linear Photometrics

Diffuser



RGB & RGBW LEDs

Maximum Output (Diffusion)

	Lm/Ft	Wt/Ft	Lm/Wt
RGB (all on)	123	9.4	6.0
White	467	6.8	8.4
RGBW (all on)	617	16.2	38.0

Output adjustable with DMX-512 Control

* Consult factory for High Output White channel 1200+ Lm/Ft
** Does not apply to Tunable White
*** See Starfire website for Product Limited Warranty

IP 65

STARFIRE LIGHTING, INC.
7 Donna Drive, Wood-Ridge, NJ 07075
starfirelighting.com

P 201.438.9540
F 201.438.9541

All designs and drawings are the property of STARFIRE LIGHTING, INC. We reserve the right to make changes to specifications and approved designs at any time without notice to facilitate manufacturing methods to the extent that such changes do not compromise design integrity. All performance specifications are subject to +/- 10% deviation.