

Low Voltage Power Supply

VersaLux

Series VLW

MR16
MR16 LED
ALR37

These state of the art power supplies incorporate very efficient, low weight toroidal transformers and are equipped to operate with dual input voltages.

Features

- Input: 120V/277V
- Single Output Secondary Voltage: 12V
- Toroidal transformer
- Transformer can be loaded up to the maximum rating
- Epoxy encapsulated transformer resulting in silent operation, eliminating long term corrosion and rusting at the connections
- Powder coated textured paint finish
- Easy opening case with knock-outs for hardwiring
- Auto resettable In-line primary overload protection
- In-line secondary magnetic breaker to protect against short circuit and overloading
- 50 amp terminal boards on the output for ease of installation
- Labeling and complete operating instructions supplied
- UL listed to U.S. and Canadian safety standards



12 Volt Transformers

Cat No.	VA Rating	Primary Voltage	Secondary Voltage	Dimensions (LxWxH)	# of Breakers	Amperage Rating	Weight
VTR-75-12V	75	120/277	12	8.75" x 4.375" x 4.25"	0	-	8 Lbs
VTR-150-12V	150	120/277	12	8.75" x 4.375" x 4.25"	1	12.5	8 Lbs
VTR-300-12V	300	120/277	12	8.75" x 4.375" x 4.25"	1	25	10 Lbs
VTR-600-12V	600	120/277	12	9.5" x 5.375" x 5.125"	2	25	16 Lbs
VTR-900-12V	900	120/277	12	10.5" x 6.125" x 6"	3	25	26 Lbs
VTR-1200-12V	1200	120/277	12	11.625" x 7" x 6"	4	25	26 Lbs